



EN 13984:2013

Declaration of Performance

According to Annex of Regulation (EU) No. 574/2014
Nr DoP 3-25072024-76
for the product

PRIVATE LABEL ALU 180 / Eurovent **STANDARD ALU 180**

1. Product type: unique identification code of the product type	3-25072024-76
2. Intended use or uses of the construction product	Flexible waterproof product, made of synthetic materials and rubber, for water vapor penetration control.
3. Manufacturer	Eurosystem Polska Sp. z o.o. Sp. K. Wiejska 13, 46-055 Przywory, Poland VAT PL 9372516153
4. Authorized representative	Not relevant
5. System or systems of assessment and verification of constancy of performance	System 3 i 4
6. Harmonized specification(s). Notified body(ies).	EN 13984:2013 Technický A Skúšobný Ústav Stavebný, N.o.Studená 967/3, 821 04 Bratislava - Ružinov- Ružinov, Slovensko, notified body identification number: 1301. Test report: 90-15-0034

7. Declared performance

CHARACTERISTIC	HARMONIZED TECHNICAL SPECIFICATION	VALUES
Reaction to fire	EN 13984:2013	E
Resistance to water penetration	EN 13984:2013	Meets requirements at 2kpa
Water vapour transmission	EN 13984:2013	$\geq 584,7 \cdot 10^{-9} \text{m}^2 \cdot \text{sPa/kg}$
Impact resistance	EN 13984:2013	NPD
Water tightness of seams	EN 13984:2013	NPD
Tensile strength MD	EN 13984:2013	$\geq 180 \text{ N/50 mm}$
Tensile strength CD	EN 13984:2013	$\geq 90 \text{ N/50 mm}$
Elongation MD	EN 13984:2013	$\geq 7,1\%$
Elongation CD	EN 13984:2013	$\geq 3\%$
Tearing Resistance MD	EN 13984:2013	$\geq 70 \text{ N}$
Tearing Resistance CD	EN 13984:2013	$\geq 65 \text{ N}$
Durability		
Ageing	EN 13984:2013	Meets requirements
Chemical resistance	EN 13984:2013	Meets requirements
Dangerous substances	EN 13984:2013	NPD

8. The performance of the above stated product is in conformity with the declared performance. This declaration of Performance is issued in accordance with the Regulation (UE) nr 574/2014 under the sole responsibility of the manufacturer specified in this declaration.

Marcin Świerta
President



Przywory, 20.09.2024 r.